






A
B
C
D
E
F
G
H



SCHEMATIC

- 1. Material/Plated
 - 1.1 Sealed Rubber:Silicone Rubber
 - 1.2 Cover:Stainless steel
 - 1.3 Contact:Copper Alloy,Silver Plated
 - 1.4 Terminal:Copper Alloy,Silver Plated
 - 1.5 Base:PA,Black
- 2. Electrical Performance
 - 2.1 Rated Voltage: 12V AC
 - 2.2 Rated Current: 50mA
 - 2.3 Contact Resistance: 100mΩ Max.
 - 2.4 Insulation Resistance: 100MΩ Min.
 - 2.5 Dielectric Strength: 250V AC
- 3. Mechanical Performance
 - 3.1 Operating Force: 250±50gf
 - 3.2 Travel: 0.35±0.15mm
 - 3.3 Durability: 100,000 Cycles
- 4. Operating Temperature: -25° C To +85° C



P. C. B LAYOUT

					DRAWN	Tom	2018-06-05	DIMENSION TOLERANCE X.X ±0.35 X.XX ±0.25 X.XXX ±0.15 GENERAL ANGLE: ±3° UNIT: mm	东莞市神久电子科技有限公司 Dongguan Shenjiu Electronic Technology Co., Ltd	
					CHECKED	Ango	2018-06-05			
					APPROVE	Kevin	2018-06-05		PART NO.	TD-93XA
					SCALE: N/A	SHEET: 1 OF 1			DWG. NO.	
REVISIONS A NEW RELEASE Tom 2018-06-05 REV. DESCRIPTION ECN NO. NAME DATE										